

# Assessment of modern shoreline transformation rates on the banks of one of the largest reservoirs in the world (Kuibyshev reservoir, Russia) using instrumental methods

Oleg P. Yermolayev<sup>1</sup>, Bulat Usmanov<sup>1</sup>, Artur Gafurov<sup>1</sup>, Jean Poesen<sup>2</sup>, and Evgeniya Vedeneeva<sup>1</sup>

<sup>1</sup>Kazan Federal University

<sup>2</sup>KU Leuven

July 9, 2021

## Abstract

The study object is the Kuibyshev reservoir. The objective is to quantitatively assess reservoir bank landslides and shoreline abrasion in active zones based on the integrated use of modern instrumental methods. Different approaches are used to assess the intensity of landslide and abrasion processes: the specific volume and material loss index, the planar displacement of the bank scarp, and the planar-altitude analysis displacements of soil masses based on the analysis of slope profiles. Shoreline position for the past periods (1958, 1985, and 1987) was obtained from archival aerial photography data; data for 1975, 1993, 2010, 2011, and 2012 were obtained from high-resolution satellite image interpretation. Field surveys of these geomorphic processes at the study areas in 2002, 2003, 2005, 2006, 2014 were carried out using total stations; in 2012-2014 using terrestrial laser scanning and a UAV survey in 2019. The monitoring of landslide processes showed that the rate of volumetric changes at Site 1 remained rather stable during the measurement period with net material losses of 0.03-0.04 m<sup>3</sup>/m<sup>2</sup>/year. The most significant contribution to the average annual value of material loss was by snowmelt runoff. The landslide scarp retreat rate at Site 2 showed a steady decreasing trend, due to partial overgrowth of the landslide accumulation zone resulting in its relative stabilization. The average long-term landslide scarp retreat rate is 2.3 m/year. In recent years, landslide control measures realized at this site have reduced the landsliding intensity by more than 2.5 times to 0.84 m/year

## Assessment of modern shoreline transformation rates on the banks of one of the largest reservoirs in the world (Kuibyshev reservoir, Russia) using instrumental methods

*Yermolaev O.<sup>1,2</sup>, Usmanov B.<sup>1</sup>, Gafurov A.<sup>1</sup>, Poesen, J.<sup>3,4</sup>, Vedeneeva E.<sup>1</sup>*

<sup>1</sup> *Kazan Federal University Department of the Landscape Ecology, Kazan, Russia*

<sup>2</sup> *Belgorod State National Research University, Belgorod, Russia*

<sup>3</sup> *Department of Earth and Environmental Sciences, KU Leuven, Leuven, Belgium*

<sup>4</sup> *Institute of Earth and Environmental Sciences, UMCS, Lublin, Poland,*

*Keywords: bank erosion – landslide – remote sensing – TLS – UAV*

**Abstract.** The study object is the Kuibyshev reservoir (Volga River basin, Russia) – the largest in Eurasia and the third in the world by area (6150 km<sup>2</sup>). The objective is to quantitatively assess reservoir bank landslides and shoreline abrasion in active zones based on the integrated use of modern instrumental methods (i.e. terrestrial laser scanning, unmanned aerial vehicle, remote sensing and a global navigation satellite system). A methodology for the application of different methods of instrumental assessment of abrasion and

landslide processes is given. Different approaches are used to assess the intensity of landslide and abrasion processes: the specific volume and material loss index, the planar displacement of the bank scarp, and the planar-altitude analysis of displaced soil masses based on the analysis of slope profiles. Shoreline position for the past periods (1958, 1985, and 1987) was obtained from archival aerial photo data; whereas data for 1975, 1993, 2010, 2011, and 2012 were obtained from high-resolution satellite image interpretation. Field surveys of these geomorphic processes at the study areas in 2002, 2003, 2005, 2006, 2014 were carried out using Trimble M3 and Trimble VX total stations (2014); in 2012-2014 using terrestrial laser scanning and a UAV survey in 2019. The monitoring of landslide processes showed that the rate of volumetric changes at Site 1 remained rather stable during the measurement period with net material losses of 0.03-0.04 m<sup>3</sup>/m<sup>2</sup>/year. The most significant contribution to the average annual value of material loss was by snowmelt runoff. The landslide scarp retreat rate at Site 2 showed a steady decreasing trend, due to partial overgrowth of the landslide accumulation zone resulting in its relative stabilization. The average long-term landslide scarp retreat rate is 2.3 m/year. In recent years, landslide control measures realized at this site have reduced the landsliding intensity by more than 2.5 times to 0.84 m/year.

## 1. Introduction

Creating reservoirs is known to develop and support several industries: i.e. electricity, agriculture, water transport, fisheries, recreation and tourism. At the same time, their creation leads to a fundamental restructuring of natural systems: river water flow and regime, bedload and suspended sediment yield are changed, a unique microclimate is created and landscapes are transformed (Yermolaev & Usmanov, 2014; Yermolaev *et al.*, 2015; Nicu *et al.*, 2019). The intensity of exogenous processes acting on the shore and banks increases by orders of magnitude due to the water surface area increase. This very complex of relief-forming processes (together with erosion and gravitational processes) is often called bank transformation when dealing with water reservoirs. Among all modified shores of water reservoirs in Russia, approximately 78% are destroyed by abrasion type, and the remaining 22% – by abrasion-landslide, abrasion-karst, and other types of erosion processes (Usmanov *et al.*, 2018; Gafurov & Yermolayev, 2020). When the banks are destroyed, a large sediment volume enters the reservoir. This leads to rapid siltation, reduction of water depths, and environmental degradation of the reservoir.

Exogenous geomorphic processes and their monitoring on the shores of water reservoirs have long been conducted (Degraff *et al.*, 1980). A large number of different research methods have been used for this purpose (Scaioni, 2015). Most often, the shoreline bank dynamics are evaluated, and there is limited quantitative data on the different exogenous processes, their intensity, and the particularities of soil transport on slopes. This is mainly due to poor field accessibility for making observations at the shoreline banks and for installing a reference point network (steep banks, high water level near the shore, bank collapse, crumbling, and landsliding). New opportunities for assessing the rate of shoreline modification by exogenous processes, particularly for shoreline areas that previously were difficult to access have emerged with the appearance of new instrumental methods (laser scanners, UAVs, remote sensing, etc.). Simultaneously, a large diversity of water reservoir types and natural-anthropogenic conditions shaping their banks has resulted in a specific spectrum of exogenic processes. This makes data generalization and spatial extrapolation difficult.

The objective of this study is to better understand shoreline and bank dynamics of the Kuibyshev reservoir – one of the largest reservoirs in the world. Research focuses on shoreline abrasion and landslide processes as the most significant exogenous natural hazards of bank modification. Attention to these processes has increased because a significant number of settlements, religious buildings, cattle burial grounds, and infrastructure (oil and gas pipelines, roads, power lines, etc.) located on the reservoir shores. The shoreline abrasion and landslide processes on the banks near settlements often leads to emergencies: i.e. destruction of buildings, infrastructures, communications, disturbance and total loss of (agricultural) lands bordering the reservoir. Shore transformation processes are still going on at a high rate even though the engineering project predicted the attenuation of these processes in 20 years after the reservoir creation. In this connection, it is necessary to develop effective methods to monitor these dangerous exogenous geomorphic processes. The objective of this study is therefore to assess quantitatively the rates of shoreline abrasion and landsliding using modern

instrumental methods. The study sites for shoreline process dynamics were selected by the Ministry of Natural Resources and Ecology of the Russian Federation and the Federal Agency for Water Resources. These government agencies identified areas of the Kuibyshev reservoir banks with the most significant exogenous natural hazards for human settlements and infrastructure.

## 1.1 Research methods for landslide processes

At present, there is a large range of methods for monitoring and estimation the intensity of exogenous processes (Savvaïdis, 2003; Tsai *et al.* , 2012; Pradhan, 2017; Gafurov *et al.* , 2018; Usmanov *et al.* , 2018; Gupta & Shukla, 2018; Mertens *et al.* , 2018). These mainly consist of collecting instrumental topographic surveys and remote sensing data, allowing the study of slope processes over several decades. In order to assess the rates of geomorphic processes occurring on the reservoir shores, this study applied alongside traditional methods (topographic field surveys) a set of modern methods: i.e. terrestrial laser scanning (TLS), unmanned aerial vehicle UAV, remote sensing and a global navigation satellite system (GNSS). These techniques allow a quickly recording with a high accuracy for determining of the shore process rates and displaced material volumes by landslides. After a critical evaluation of the various methods and a description of the study area, we report on the methods applied in this study.

### 1.1.1 Traditional geodetic methods for studying landslide processes

The use of traditional theodolite and total station measurements can achieve millimeter-scale errors when determining point coordinates (Savvaïdis, 2003). Generally, a relative coordinate system is used for the survey which creates a problem when comparing such data with geo-referenced data sources. It is therefore necessary to recalculate the position of the field points to allow plotting these into the global coordinate system by specific position of the reference points (Gupta & Shukla, 2018).

The advantage of this surveying method is its high accuracy. The disadvantage is that the surveys take a long time; therefore, a limited number of points located in accessible places are selected. The development of TLS, UAVs, allowing to take large amounts of data in a short time, precisely and in detail describing the surveyed surface, makes the classical topographic survey an outdated approach (Barbarella & Fiani, 2013).

A limited control of processes operating within the landslides and the displaced ground masses are the most significant disadvantages of traditional approaches. None of these methods provides comprehensive information on quantitative characteristics and mechanism of erosion processes on slopes. Thus, the most effective methods for studying inaccessible slopes with landslides are the repeated morphological surveys with accurate referencing of multi-temporal data.

### 1.1.2 Ground-based laser scanning

Compared with traditional methods (aerial photography, ground photogrammetric survey, field studies), laser scanning has several advantages. Very precise results make it possible to estimate the intensity of slope processes, and estimate the age of landslide bodies (Monserrat & Crosetto, 2008; Dunning *et al.* , 2009), to build detailed three-dimensional models and evaluate the slope stability (Viero *et al.* , 2010). One of the essential uses of ground-based laser scanning is to study the dynamics of slope processes. The study of relief dynamics requires repeated measurements of the object under study and their comparison with previous data, which requires geodetically accurate referencing provided by modern ground-based laser scanning technologies (Barbarella *et al.* , 2015; Gafurov *et al.* , 2016; Yermolaev *et al.* , 2018).

Fundamentally different technology for scanning results of georeferencing was proposed in 2014 by a group of Polish researchers. A network of ground control points was organized with the use of the differential global positioning system (DGPS) (Kociuba *et al.* , 2014). The georeference accuracy, taking into account the DGPS receiver error, was 26 cm. In 2015, the same research team carried out laser scanning to monitor gully processes in a relative coordinate system, which led to an increase in the accuracy of scans adjustment by two orders (Kociuba *et al.* , 2015). Similar studies were carried out in 2008-2010 in Spain by the Jimenez-Peralvarez scientific team (Palenzuela *et al.* , 2016) and by Swiss scientists under the leadership of

M. Franz in 2012 (Franz *et al.* , 2016). The combination of different technologies made it possible to achieve georeferencing accuracy within 11 mm in plan and 17 mm in height.

Studies of landslides near water bodies are mainly carried out on the coasts of seas and oceans (Spreafico *et al.* , 2015). Few scientific studies have been devoted to the monitoring of hazardous processes on slopes bordering reservoirs. Several publications on the Three Gorges Reservoir in China, created in 2003, stand out (Wang *et al.* , 2015; Nicu *et al.* , 2019; Zhang *et al.* , 2020; Guo *et al.* , 2020). In contrast, in Russia, there are many studies devoted to studying geomorphic processes on the banks of large reservoirs, because of the large-scale construction of hydroelectric power plants in the middle of the last century (Starodubtsev, 2012; Babicheva & Rzetala, 2013; Kalinin *et al.* , 2015; Bondur *et al.* , 2019; Mazaeva *et al.* , 2019; Nikonorova *et al.* , 2019).

### 1.1.3 The use of UAVs

Although many sensors are currently available on ground, airborne, and space-based platforms, methods using unmanned aerial vehicles are rapidly developing among all modern methods for exogenous processes monitoring (Marzloff & Poesen, 2009; Marzloff *et al.* , 2011). The possibility of obtaining three-dimensional (3D) information about the terrain with high accuracy and spatial resolution opens up new horizons for studying landslide processes (Gafurov, 2017; Eker *et al.* , 2018; Gafurov, 2021). The first studies involving UAV for exogenous processes monitoring started relatively recently. The authors note the perspective of photogrammetry technology; however, they conclude that at that time, DEMs obtained using budget airborne surveys are not accurate enough to study the rill network, in contrast to DEMs obtained using ground-based laser systems, which allow a better reconstruction of the soil surface topography.

Particular attention should be given to methodological and technical works in which UAVs are compared with other, already proven methods. For example, when comparing models obtained by TLS and UAV with the results of total station surveys, in grass vegetation covers, the UAV gives a model even more accurate than the TLS (Gruszczyński *et al.* , 2017; Gafurov, 2018). When comparing the TLS and UAV models, the errors vary within 5 mm (Eltner *et al.* , 2013) from using the ICP method. For erosion field calibration stand, the average error was 0.03 mm with a standard deviation of 5 mm (Nouwakpo *et al.* , 2016; Wilkinson *et al.* , 2016).

## 2. Study area

The Kuibyshev reservoir, built on the Volga River, is the largest in Eurasia and the third-largest in the world, after Volta (Ghana) and Smallwood (Canada) reservoirs. It is located in the central part of the Middle Volga basin at the intersection of the forest and forest-steppe landscape zones of the Volga uplands and the Low Volga (Yermolaev, 2017) (Figure 1). The geographic coordinates of the reservoir's borders are 56°10' - 53°30' N, 47°30' - 49°30' E. There are three orographic regions within its basin: Volga Upland, Vyatka Predkamyie, Low Volga. The research was conducted within the Volga Upland at the right side of the reservoir; its banks are steep and precipitous. Absolute heights are 175-215 m in the north and 250-270 m in the south. The maximum altitudes are confined to the Zhigulevskiy Mountains (349 m).

The reservoir was formed on October 31, 1955 following the Volga River damming by Kuibyshev hydroelectric complex. The reservoir reached its full reservoir level (FRL) of 53 m a.s.l. during the 1957 high waters. Its total capacity is 57.3 km<sup>3</sup>, its water surface area equals 6150 km<sup>2</sup> and its total length along the Volga river is 510 km and 280 km along the Kama river. Its width varies between 2 and 27 km with a maximum of 38 km at Kamskoe Ustye. Average water depth is 9.4 m, maximum – 41 m. The length of the coastline is 2604 km, minimum navigation level is 49.00 m. The reservoir is a seasonal flow regulation storage: the average annual conditional coefficient of water exchange is 4.3.

The inflow and outflow discharges are asynchronous, and their ratio determines the reservoir filling and drawdown. The reservoir fills up to the maximum level during spring floods, while in autumn and winter the level is at its lowest position. The annual amplitude of level fluctuations is about 6 m. The average runoff velocity in the reservoir is 2-10 cm/sec, depending on the value of transit flow and the live cross-sectional

area. The morphological structure of the reservoir is a system with lake-like expansions. This reservoir serves several economic sectors: i.e. energy, water transport, agriculture, fisheries, industrial and municipal water supply.

Two sites on the right bank of the Kuibyshev reservoir near Kamskoe Ustye village (Republic of Tatarstan) were selected to evaluate the intensity of shoreline abrasion and landsliding. The sites were selected based on their representativeness in terms of geological-geomorphological and landscape conditions for the study area. In addition, the economic aspect was taken into account since there is a threat of partial destruction of the buildings and infrastructure facilities according to the state authorities of the Russian Federation.

**At site 1** not only landsliding but also abrasion processes at the shoreline have developed. The site is located on the right bank 30 m upstream of the Volga river pier (Figure 2).

The landslide and abrasion process acting on the bank are observed here. In the upper part of the slope, composed of heavy and middle deluvial-solifluction loams, collapse and sliding of earth blocks of different volumes towards the shoreline occur. At the foot of the abrasion ledge in some places, there are outcrops of the Kazanian age deposits, i.e. clayey-melty gray pack of rocks of the upper Permian system.

The landslide has a frontal shape, its length is 32.0 m and its width is 55 m (total area is 1760 m<sup>2</sup>). An abrasion scarp has formed in the lower part of the slope with traces of landslides and washout. In aslope profile, the landslide body itself is well identified in the upper part with a head scarp and in the lower part a terrace-shape section. The beach is 2.5-5.0 m wide and is composed of sand-and-shingle material. The abrasion section at the lower part of the slope erodes and collapses; soil blocks slide through cracks to the shoreline where they are eroded by water. Wavebreaking caves are practically absent. Other exogenous processes are acting on the slope in addition to the dominant landslide process. There are rills and ephemeral gullies in the upper part of the slope and gravitational processes (collapse and crumbling) in the middle and lower part. However, they are of subordinate importance in terms of active slope processes.

**At site 2**, a large landslide cirque has formed as a result of mass movement processes. Here, the landslide-abrasion type of coastal escarpment is observed. Due to changes in groundwater outflow caused by water level rise, a sliding landslide develops (Figure 3), forming a large landslide cirque.

The upper part of the landslide processes led to the destruction of the old cemetery. Landslide length is 173 m and its width is 110 m (total area is 13900 m<sup>2</sup>). The height of the landslide edge is 14,7 m, the steepness is 90 degrees. The body of the landslide is hilly and canopy-shaped. The upper landslide scarp is close to the buildings.

The lower northern part of the landslide body is affected by very active slope subsidence of the earth block type. The slope is composed of deluvial-solifluction loams with the vertical type of clastic-block structure, blocks with shrub and woody vegetation are collapsing along the cracks.

The height of the blocks is 5-6 m, width up to 7-8 m. The soil surface of the old cemetery is deformed due to cracking and subsidence. The landslide bodies are located further down the slope, moving towards the Volga at low speed; their hilly surfaces are overgrown with willow, american maple, saltbush, common nettle and coltsfoot. Behind the edge of this landslide body is the landslide cirque. Its southwestern cliff destroys the old cemetery. Numerous human remains emerge from a depth of 1.5-2 m in the landslide escarpment. In the lower part of the slope, an abrasion scarp with traces of breakwater caves can be observed.

In 2018 to the south of the study Site 2, a shore reconstruction was carried out to organize a recreational area near the camping base (Figure 4). As a result of excavation works and re-organization of access roads to the camping base pier, the south-eastern part of the studied landslide cirque and landslide body was leveled and sodded (Figure 4b). As a result, this fragment of the landslide ledge was excluded from further analysis. However, the works carried out to improve the sloping area did not reduce the intensity of geomorphic processes, and the works on slope stabilization had to continue.

### 3. Materials and methods.

Various sources of information and observation methods were combined to estimate the intensity of abrasion and landslide processes at the reservoir shores. Shoreline positioning for the past periods (1958, 1985, 1987 and 1993) was obtained from archived aerial images (Kazan University Library); data for 1975, 2010, were obtained from satellite imagery (Table 4) interpretation. Field measurements at the study sites were conducted in 2002, 2003, 2005, 2006 using Trimble M3 total station (2014). Since traditional methods mainly provide information about the planar displacement of the landslide scarp edge, the laser scanning method was additionally used in 2012-2014 to study the volume changes in hard-to-reach and hazardous areas. A Trimble GX TLS used as scanning equipment (Figure 5, Table 1). From 2019 onwards field surveys include a DJI Phantom 4 UAV survey.

Since the slope processes at the studied sites develop differently – a block landslide at Site 1 and a landslide cirque at Site 2, the methodological approaches for their study were also different.

### 3.1 Site 1.

At Site 1, an analysis of the abrasion-slope DEM obtained from ground-based laser scanning in 2012-2014 and UAV imagery in 2019 was chosen as the main method of shoreline deformation (Table 2).

The results of scanning were processed in the Trimble Realworks software. The obtained point clouds were exported to the Golden Software Surfer software, whereby triangulation with linear interpolation of the DEM with a spatial resolution of 0.1 m was created. The calculation of volume change was performed using the Volume tool. According to laser scanning results, a specific indicator such as the volume of eroded soil per unit area ( $V./S$ ,  $m^3/m^2$ ) was used to estimate the intensity of landslide processes.

Photogrammetric processing of UAV survey results was performed in Agisoft Photoscan software. A combined approach was used to align the point clouds obtained by laser scanning and unmanned aerial vehicle. Since the main survey using terrestrial laser scanning was carried out in the relative coordinate system and the UAV data in the global coordinate system, it was decided to recalculate the latter in the relative coordinate system. At the first stage, common stable areas were singled out on the point clouds obtained from different sources: i.e. elements of the pier, corners of buildings and bank protection structures. Based on the obtained matches, the point clouds were re-aligned using the ICP method to minimize the georeferencing error (Table 3). The obtained errors are considered to be permissible in landslide process studies (Peppas *et al.*, 2016; Zang *et al.*, 2019).

### 3.2 Site 2.

Analysis of landslide scarp retreat was chosen as the primary method for studying bank transformation at Site 2. A wide range of data was used to perform this task (Table 4).

Archived aerial and satellite images were used to study the changes in the shoreline position, and modern satellite images were used as base for their spatial reference. Since 2002, a topographic survey was carried out in a relative coordinate system. A network of reference points was created, to provide multi-term survey. The reference points' coordinates were determined using a Trimble M3 total station. A GNSS receiver using real-time kinematic corrections was used to transform the obtained results into the global coordinate system in 2012.

The Digital Shoreline Analysis System (DSAS), as an extension module of the ArcGIS software, was used to quantify shoreline displacement (Himmelstoss *et al.*, 2018). This module is effective for simplifying the analysis of shoreline position changes (Oyedotun, 2014; Nicu, 2021). The 1958 shoreline (immediately after filling the reservoir) was taken as a baseline. Following parameters were selected: distance between the transects – 15 m, search radius –300 m. Based on the obtained transects, shoreline indicators such as linear retreat rate (m/year), shoreline displacement (m) were automatically calculated.

## 4. Results and Discussion

### 4.1. Observations at site 1

Assessment of landslide and shoreline abrasion intensity at Site 1 is based on the volume of material displaced per unit area. According to the laser scanning results, changes were evaluated in the upper part of the slope, where a block type landslide was developing, and in the lower part, where an abrasion scarp was formed as a result of wave wash (Figure 6). The evolution of the situation at study site 1 was analyzed by comparing the results of laser scanning (Table 5) and those obtained during the 2019 UAV survey (Table 6).

Ground displacements in the abrasion scarp area vary independently of the seasons, which is explained by the water level fluctuations of the reservoir. First, there is an accumulation of soil in the lower part of the slope due to landslide processes. In the case of high-water levels, the soil is eroded by wave abrasion. During water drawdown the foreshore width does not allow the waves to erode the shore, and material accumulates again at the foot of the slope. This explains why denudation near the abrasion scarp prevails in 2012-2013, and accumulation processes prevailed in 2013-2014.

In general, for study site 1 denudation processes are dominant during the observation period (Table 8). Volume of landslide changes per unit area showed that intra-season and inter-annual dynamics of the process are irregular. The high intensity of the denudation process in the autumn-winter period of 2013 is noted because of a smooth increase of solar radiation and, as a consequence, low evaporation passing into snowmelt runoff. The comparable rates of the denudation process in the summer-autumn period of 2013 and autumn-winter period of 2014 are explained by a significant erosive ( $>10$  mm/day) rainfall and, in contrast, by a less erosive winter precipitation (Figure 7). However, despite the fundamentally different patterns of intra-annual variability of denudation processes, the inter-annual net material loss at site 1 remains, rather constant (ca.  $-0.03$  m<sup>3</sup>/m<sup>2</sup>).

The analysis of the dynamics of transverse profiles (Figure 8 Profile 1) showed that in the zone of block landslide development, the mass movement in the summer-autumn period is smaller than in the autumn-summer period. In the summer-autumn period of 2013, the landslide body did not change its position. Displacements of masses occur mainly during the snowmelt period. So, in the autumn-summer period of 2013, the landslide mass moved downslope by 4 m, and in 2014 by 3 m in plan.

The graphs show that in November 2012, there was an accumulation of soil masses on the abrasion part of the bank slope. From November 2012 to July 2013, the accumulated material was intensively eroded. The reduction of the process intensity characterizes the summer-autumn period of 2013. Significant re-activation was observed in the period from November to June 2014.

A significant difference is observed between the 2012-2014 and the 2019 slope profiles. The landslide body is not seen on the 2019 profile which is almost straight. Over the last five years, the landslide body has been completely transformed, the profile of the slope has reached a dynamic equilibrium and has become linear. The average thickness of the transformed soil layer on the flattened sections was 1.5 m or 0.5 m/year during 2012-2014 and 2 m or 0.4 m/year during 2014-2019 (Figure 9).

Based on the 2003-2006 survey, the authors recommended to install landslide-control measures, directed to protect the pier under construction. The essence of the measures consisted in the modelling of the landslide slope with subsequent flattening at 2007, installing engineering structures at the foot of the slope to protect it from wave action and to prevent the development of abrasion processes. The implemented measures turned out to be very effective. At present (2019), no landslide reactivation processes are observed on the treated part of the slope, which can be seen in profile 2 (Figure 8).

#### 4.2. Observations at site 2.

Landsliding was initiated at this site after the Kuibyshev reservoir filling in 1957, as shown in the archive images (Figure 10). On the 1958 image at the shore scarp foot small erosion forms of rill type can be observed. The 1985 image shows the slope transformation due to abrasion and landslide processes along the bank front, reaching the gully's left bank in the eastern part of the site. In 1987, the shoreline scarps began to take a circular shape, and later on, the upper part of the slope was transformed by landslide processes. In the lower part, a landslide body is formed, which is gradually eroded due to abrasion by wave erosion.

The digitized scarp lines for different periods – (i.e. 1958-1975, 1975-1985, 1985-1987, 1987-1993, 1993-2002, 2002-2019) were analyzed to calculate the rate of landslide scarp retreat in DSAS. This is primarily due to the change in the slope’s horizontal shape and transition into a cirque type of landslide. The plan shape of the scarp line was gradually changing from a line to an arc, which would introduce distortions when making measurements in the DSAS module. Therefore, it was decided to plot lines perpendicular to the baseline of the corresponding period separately.

In general, the average rate of landslide slope retreat varies in the range of 1-2 m/year throughout the study period (Table 7). The period of 1985-1987 stands out as a landslide block moved downslope, and subsequently, the landslide changed to the cirque type and the scarp retreat rate decreased (Figure 11). The analysis of the landslide scarp retreat rate between 2002 and 2019 was conducted from the 2002 line because of the stabilization of the plan shape of the landslide scarp in subsequent years. This is partly due to the excavation works to improve the surrounding area, which leads to a reduction of the landslide scarp retreat rate to 0.84 m/year in 2019 which transferred the landslide to the moderately hazardous landslide category (Ragozin & Burova, 1993).

It should be noted that the study in 2002-2006 was carried out according to the state program, the aim of which was to analyze the landslide processes on both sites and to evaluate their hazard for nearby inhabited and uninhabited constructions. As a result of this study, several recommendations for landslide control measures were formulated. At Site 1, following the recommendations made, shore protection constructions were installed, which made it possible to stabilize the landslide processes above it completely. Unfortunately, a shore protection dam was not installed along the slope’s entire length (see Figure 2), which made it impossible to stabilize the entire landslide section. At Site 2, shore protection and improvement works were not organized until 2018-2019. When the camping base was constructed, approximately one-third of the landslide cirque was reduced, which also resulted in a reduction of the landsliding intensity (Figure 11).

### 4.3. Discussion

Using different remote sensing methods allows quantitative assessments of several exogenous processes at different scales and qualitative levels. Landslide processes may have different appearances, and their assessment requires different approaches (Broeckx *et al.*, 2019, 2020). Each tool solves the problem differently. Volumetric landslide changes evaluation is possible by calculating the difference of 3D models obtained by terrestrial scanning systems and unmanned aerial vehicles. Assessment of planar displacements is possible by visual interpretation of remote sensing data and field monitoring of the boundaries of the study object using a total station survey. Satellite images, as well as simple aerial photos, do not allow to produce a volumetric picture. However, TLS does not allow to establish the exact position of the landslide body boundaries. Scanning total stations, allow to solve classical tachymetric tasks - that give the most exact position of object borders under research; and to make scanning of landslide object for the subsequent three-dimensional reconstruction. TLS helps to estimate volumetric changes with millimeter accuracy. However, when estimating landslide structures located on the banks of reservoirs, access from all sides is difficult. It may give so-called shadows – areas with no information on three-dimensional data. The UAV method has not such a disadvantage; however, even though the method allows creating three-dimensional models comparable to TLS detail and accuracy, multi-time measurements alignment is still tricky because of the UAV navigation system inaccuracies.

Nevertheless, the error of georeferencing of multitemporal models is considered to be acceptable when assessing landslide process changes because of their high intensity. Returning to the most optimal method, weighing all the advantages and disadvantages of the applied methods, it can be noted that the use of UAV to assess planar and volumetric changes on slopes allows obtaining both a three-dimensional model and a ultrahigh-resolution orthophoto, with which the retreat of the slope scarp can be monitored. However, as noted earlier, the construction of accurate difference-time maps requires high-precision positioning of the aircraft itself, which is achieved using high-precision GNSS receivers that allow making corrections in real-time kinematics or post-processing. As the established practice of using such airborne systems has shown, the best results in comparing multi-temporal data can be achieved by simultaneous use of UAV image data with high-precision positioning, taking into account corrections from the base station and ground reference



points.

The use of modern unmanned systems allows taking images with multispectral cameras that provide additional possibilities for analyzing the relationship between the spectral characteristics of rocks composing the landslide body and the intensity of the processes. However, comprehensive mathematical and statistical modeling is possible only with spatial data on fundamental factors of landslide formation – the steepness of slopes, soil texture and type of rocks, air temperature and precipitation data, especially for the winter period, groundwater depth data, and reservoir level fluctuations. However, for verification of modeling results, one needs data on currently developing landslides along the Kuibyshev reservoir banks, which is to be collected in the near future.

Active shoreline erosion currently occurs in almost all water reservoirs in Russia. In total, 36% of the shoreline of all water reservoirs in Russia is affected by these processes (Burova, 2020). Shoreline erosion is most active within large reservoirs with a capacity of more than 10 million m<sup>3</sup>. For such water bodies in the European part of Russia about 40% of shores is transformed, in Siberia - 36%, in the Far East - 35%, while in small reservoirs, located in the same regions, only 13-15% of the total shoreline is affected by shoreline erosion (Ovchinnikov & Maksimishina, 2002).

Among the large water bodies of the European part of Russia, the most affected by bank destruction are the Kuibyshev (75%), Volgograd (72%), Saratov (70%), and Gorky (65%) reservoirs, located in forest-steppe and steppe zones. More than 50% of the banks are actively retreating at the Kama and Novosibirsk reservoirs. For other water bodies in Russia, shoreline degradation usually occurs on less than 40% of the shoreline.

Analysis of actual data on linear shoreline retreat rates showed that the maximum average annual retreat rates during the first ten years of development of water reservoirs, i.e. during the first, active stage of the process development, amount to 10-20 m/year. In some years, the indicated rates of bank erosion at the first stage can be significantly higher, up to 100 m/year. Thus, in the eastern part of Kamskoye Ustie (Sites 1-2), a 70-90 m wide strip of coastline was destroyed by landslides during the first 30 years of the reservoir's existence. The average annual intensity of shoreline processes of the largest reservoirs of Russia at the second stage of development in the regime of steady-state or slowing-down deformations is, as a rule, significantly smaller and usually does not exceed 1-2.5 m/year. The data obtained at the studied site are comparable with the data of previous studies (Dedkov, 1991), conducted mainly by standard surveying methods.

Nevertheless, at some sites, recent studies show much larger values of shoreline displacement, mainly in the areas with loams. This, for example, occurs near the village of Izmeri in Spassky District, Republic of Tatarstan (55.130452, 49.469740), where maximum retreat values reach 9 m/yr, with average values of 1- 6 m/yr (Usmanov *et al.* , 2018).

Observations of coastal retreat and landslide processes have been made at the Kuibyshev reservoir (Kotlyakov *et al.* , 2007; Gaynullin *et al.* , 2014a, 2014b; Bepalova *et al.* , 2020), mainly focusing on the assessment of coastal retreat and land losses. Long-term observations of landslide processes are conducted mainly by state agencies by installing ground control points at random sections. Unfortunately, these data are not available for scientific studies and are not published.

The use of modern methodological approaches allows obtaining information on landslide processes independently, quickly, and efficiently. These allow estimating changes on the whole front of the landslide slope and dangerous areas, inaccessible to observations by traditional methods.

## 5. Conclusions

Assessment of the retreat rates of the landslide scarp is possible using both remote sensing from space and orthophoto maps obtained from UAVs and classical total station surveys. All these sources of information are interchangeable and complementary when working in the same coordinate system. The use of historical archival aerial photographs allows to assess the intensity of this land degradation process since the initiation of landslide processes.

The monitoring of landslide processes using a set of different measurement methods reveals that the rate of volumetric changes as a result of landslide processes at Site 1 has remained stable during the period of measurements and is  $-0.03-0.04 \text{ m}^3/\text{m}^2/\text{year}$ , with the most significant contribution to the average annual value being made by snowmelt runoff. The spatial dynamics of the landslide edge at Site 2 showed a steady decreasing trend of the retreat rate, beginning in 2002-2003, associated with partial overgrowth of the landslide accumulation zone and its relative stabilization. The average speed of landslide scarp retreat rate for of the entire observation period is  $2.3 \text{ m/year}$ . In recent years' landslide control measures taken in this area have reduced the landslide scarp retreat rate by more than 2.5 times to  $0.84 \text{ m/year}$ .

## Acknowledgements

The study was carried out with the support of the Russian Science Foundation (project 19-17-00064 - working methodology, preparation and analysis of data; project 20-67-46017 - mathematical and statistical data processing).

## Conflict of Interest Statement

Authors declare no conflict of interest

## References

- Babicheva VA, Rzetala MA. 2013. The main types of banks of Angara water reservoirs: Overview of the problem. *International Multidisciplinary Scientific GeoConference SGEM 1* : 195–202. DOI: 10.5593/SGEM2013/BA1.V1/S01.027
- Barbarella M, Fiani M. 2013. Monitoring of large landslides by Terrestrial Laser Scanning techniques: field data collection and processing. *European Journal of Remote Sensing 46* : 126–151. DOI: 10.5721/Eu-JRS20134608
- Barbarella M, Fiani M, Lugli A. 2015. Landslide monitoring using multitemporal terrestrial laser scanning for ground displacement analysis. *Geomatics, Natural Hazards and Risk 6* : 398–418. DOI: 10.1080/19475705.2013.863808
- Bespalova KV, Selezneva AV, Seleznev VA. 2020. Influence of the water discharge of the Kuibyshev reservoir on the dynamics of the ecosystem of the Seredysh and Bakhilovsky islands, the Volga River, Russia. *IOP Conference Series: Earth and Environmental Science 607* : 012017. DOI: 10.1088/1755-1315/607/1/012017
- Bondur VG, Zakharova LN, Zakharov AI, Chimitdorzhiev TN, Dmitriev AV, Dagurov PN. 2019. Monitoring of landslide processes by means of l-band radar interferometric observations: Bureya river bank caving case. *Issledovaniya Zemli iz Kosmosa 3–14*. DOI: 10.31857/S0205-9614201953-14
- Broeckx J, Maertens M, Isabirye M, Vanmaercke M, Namazzi B, Deckers J, Tamale J, Jacobs L, Thiery W, Kervyn M, Vranken L, Poesen J. 2019. Landslide susceptibility and mobilization rates in the Mount Elgon region, Uganda. *Landslides 16* : 571–584. DOI: 10.1007/s10346-018-1085-y
- Broeckx J, Rossi M, Lijnen K, Campforts B, Poesen J, Vanmaercke M. 2020. Landslide mobilization rates: A global analysis and model. *Earth-Science Reviews 201* : 102972. DOI: 10.1016/j.earscirev.2019.102972
- Burova VN. 2020. Abrasion Risk Assessment on the Coasts of Seas and Water Reservoirs. *Geodetski list 74* : 185–198
- Dedkov AP (ed). 1991. *Middle Volga. Geomorphological guidebook (in Russian)* . Kazan
- Degraff J, Olson E, EP O. 1980. Landslide monitoring techniques for wildland management. *J. Soil water conserv 35* : 241–242
- Dunning SA, Massey CI, Rosser NJ. 2009. Structural and geomorphological features of landslides in the Bhutan Himalaya derived from terrestrial laser scanning. *Geomorphology 103* : 17–29. DOI: 10.1016/j.geomorph.2008.04.013

- Eker R, Aydın A, Hübl J. 2018. Unmanned aerial vehicle (UAV)-based monitoring of a landslide: Gallenzerkogel landslide (Ybbs-Lower Austria) case study. *Environmental Monitoring and Assessment* **190** : 28. DOI: 10.1007/s10661-017-6402-8
- Eltner A, Mulsow C, Maas H-G. 2013. Quantitative measurement of soil erosion from TLS and UAV data. *ISPRS - International Archives of the Photogrammetry, Remote Sensing and Spatial Information Sciences***XL-1/W2** : 119–124. DOI: 10.5194/isprsarchives-XL-1-W2-119-2013
- Franz M, Carrea D, Abellán A, Derron M-H, Jaboyedoff M. 2016. Use of targets to track 3D displacements in highly vegetated areas affected by landslides. *Landslides* **13** : 821–831. DOI: 10.1007/s10346-016-0685-7
- Gafurov A. 2021. The Methodological Aspects of Constructing a High-Resolution DEM of Large Territories Using Low-Cost UAVs on the Example of the Sarycum Aeolian Complex, Dagestan, Russia. *Drones***5** : 7. DOI: 10.3390/drones5010007
- Gafurov AM. 2017. Possible Use of Unmanned Aerial Vehicle for Soil Erosion Assessment. *Uchenye Zapiski Kazanskogo Universiteta-Seriya Estestvennye Nauki* **159** : 654–667
- Gafurov AM. 2018. Small catchments DEM creation using Unmanned Aerial Vehicles. *IOP Conference Series: Earth and Environmental Science***107** : 012005. DOI: 10.1088/1755-1315/107/1/012005
- Gafurov AM, Rysin II, Golosov VN, Grigoryev II, Sharifullin AG. 2018. Estimation of the recent rate of gully head retreat on the southern megaslope of the East European Plain using a set of instrumental methods. *Vestnik Moskovskogo Universiteta, Seriya 5: Geografiya***2018-January** : 61–71
- Gafurov AM, Yermolaev OP, Usmanov BM. 2016. Assessment of the intensity of slope erosion using terrestrial laser scanning. *International Journal of Pharmacy and Technology* **8** : 14822–14832
- Gafurov AM, Yermolayev OP. 2020. Automatic Gully Detection: Neural Networks and Computer Vision. *Remote Sensing* **12** : 1743. DOI: 10.3390/rs12111743
- Gaynullin I, Sitdikov A, Usmanov B. 2014a. Destructive abrasion processes study in archaeological sites placement (Kuibyshev and Nizhnekamsk reservoirs, Russia). *International Multidisciplinary Scientific Conference on Social Sciences & Arts SGEM 2014* , 339–334. DOI: 10.5593/SGEMSOCIAL2014/B31/S9.044
- Gaynullin II, Sitdikov AG, Usmanov BM. 2014b. Abrasion processes of Kuibyshev Reservoir as a factor of destruction of archaeological site Ostolopovo (Tatarstan, Russia). *Advances in Environmental Biology***8** : 1027–1030
- Gruszczyński W, Matwij W, Ówiąkała P. 2017. Comparison of low-altitude UAV photogrammetry with terrestrial laser scanning as data-source methods for terrain covered in low vegetation. *ISPRS Journal of Photogrammetry and Remote Sensing* **126** : 168–179. DOI: 10.1016/j.isprsjprs.2017.02.015
- Guo Z, Chen L, Yin K, Shrestha DP, Zhang L. 2020. Quantitative risk assessment of slow-moving landslides from the viewpoint of decision-making: A case study of the Three Gorges Reservoir in China. *Engineering Geology* **273** : 105667. DOI: 10.1016/j.enggeo.2020.105667
- Gupta SK, Shukla DP. 2018. Application of drone for landslide mapping, dimension estimation and its 3D reconstruction. *Journal of the Indian Society of Remote Sensing* **46** : 903–914. DOI: 10.1007/s12524-017-0727-1
- Himmelstoss EA, Henderson R, Kratzmann M, Farris A. 2018. *Digital Shoreline Analysis System (DSAS)* . Version 5
- Kalinin VG, Nazarov NN, Pyankov SV, Simirenov SA, Tynyatkin DG. 2015. Activity of the Landslide on the Bank of the Kamskoe Storage Reservoir According to Stationary Measurements and GIS-Technology Application. *Geomorphology RAS* **55**. DOI: 10.15356/0435-4281-2004-4-55-62

- Kociuba W, Janicki G, Rodzik J, Stępczyński K. 2015. Comparison of volumetric and remote sensing methods (TLS) for assessing the development of a permanent forested loess gully. *Natural Hazards* **79** : 139–158. DOI: 10.1007/s11069-015-1807-6
- Kociuba W, Kubisz W, Zagórski P. 2014. Use of terrestrial laser scanning (TLS) for monitoring and modelling of geomorphic processes and phenomena at a small and medium spatial scale in Polar environment (Scott River – Spitsbergen). *Geomorphology* **212** : 84–96. DOI: 10.1016/j.geomorph.2013.02.003
- Kotlyakov AV, Shumakova EM, Artem'ev SA. 2007. Dynamics of the coastal zone of the Kuibyshev and Saratov reservoirs in the Tolyatti area and its correlation with the operation regime of the Zhigulevskaya HPP. *Water Resources* **34** : 657–662. DOI: 10.1134/S0097807807060061
- Marzolf I, Poesen J. 2009. The potential of 3D gully monitoring with GIS using high-resolution aerial photography and a digital photogrammetry system. *Geomorphology* **111** : 48–60. DOI: 10.1016/j.geomorph.2008.05.047
- Marzolf I, Ries JB, Poesen J. 2011. Short-term versus medium-term monitoring for detecting gully-erosion variability in a Mediterranean environment. *Earth Surface Processes and Landforms* **36** : 1604–1623. DOI: 10.1002/esp.2172
- Mazaeva O, Babicheva V, Kozyreva E. 2019. Geomorphological process development under the impact of man-made reservoir operation, a case study: Bratsk reservoir, Baikal-Angara hydroengineering system, Russia. *Bulletin of Engineering Geology and the Environment* **78** : 4659–4672. DOI: 10.1007/s10064-018-1428-x
- Mertens K, Jacobs L, Maes J, Poesen J, Kervyn M, Vranken L. 2018. Disaster risk reduction among households exposed to landslide hazard: A crucial role for self-efficacy? *Land Use Policy* **75** : 77–91. DOI: 10.1016/j.landusepol.2018.01.028
- Monserrat O, Crosetto M. 2008. Deformation measurement using terrestrial laser scanning data and least squares 3D surface matching. *ISPRS Journal of Photogrammetry and Remote Sensing* **63** : 142–154. DOI: 10.1016/j.isprsjprs.2007.07.008
- Nicu I, Usmanov B, Gainullin I, Galimova M. 2019. Shoreline Dynamics and Evaluation of Cultural Heritage Sites on the Shores of Large Reservoirs: Kuibyshev Reservoir, Russian Federation. *Water* **11** : 591. DOI: 10.3390/w11030591
- Nicu IC. 2021. Is digital shoreline analysis system “fit” for gully erosion assessment? *CATENA* **203** : 105307. DOI: 10.1016/j.catena.2021.105307
- Nikonorova IV, Petrov NF, Gumenyuk AE, Ilyin VN. 2019. Sustainable use of natural resources in a hazardous landslide slopes of Cheboksary reservoir (river Volga). *IOP Conference Series: Materials Science and Engineering* **663** : 012043. DOI: 10.1088/1757-899X/663/1/012043
- Nouwakpo SK, Weltz MA, McGwire K. 2016. Assessing the performance of structure-from-motion photogrammetry and terrestrial LiDAR for reconstructing soil surface microtopography of naturally vegetated plots. *Earth Surface Processes and Landforms* **41** : 308–322. DOI: 10.1002/esp.3787
- Ovchinnikov GI, Maksimishina YS. 2002. The importance of geological-geomorphological factors in the development of abrasion processes on the coasts of the Bratsk Reservoir, in the SE part of Russia. *Landform Analysis* **Vol. 3**
- Oyedotun TDT. 2014. Shoreline geometry: DSAS as a tool for Historical Trend Analysis. *Geomorphological Techniques (Online Edition)*
- Palenzuela JA, Jiménez-Perálvarez JD, El Hamdouni R, Alameda-Hernández P, Chacón J, Irigaray C. 2016. Integration of LiDAR data for the assessment of activity in diachronic landslides: a case study in the Betic Cordillera (Spain). *Landslides* **13** : 629–642. DOI: 10.1007/s10346-015-0598-x

- Peppas MV, Mills JP, Moore P, Miller PE, Chambers JE. 2016. Accuracy assessment of a UAV-based landslide monitoring system. *ISPRS - International Archives of the Photogrammetry, Remote Sensing and Spatial Information Sciences* . paper presented at the XXIII ISPRS Congress, Commission V **XLI-B5** : 895–902. DOI: 10.5194/isprsarchives-XLI-B5-895-2016
- Pradhan B. 2017. *Laser scanning applications in landslide assessment* . Springer
- Ragozin AL, Burova VN. 1993. A method for approximate forecast of reservoir bank destruction. *Journal of Hydrotechnical Construction* **10** : 20–26
- Savvaidis P. 2003. Existing landslide monitoring systems and techniques. *From Stars to Earth and Culture* 242–258
- Scaioni M (ed). 2015. *Modern Technologies for Landslide Monitoring and Prediction* . Springer Berlin Heidelberg: Berlin, Heidelberg. DOI: 10.1007/978-3-662-45931-7
- Spreafico MC, Perotti L, Cervi F, Bacenetti M, Bitelli G, Girelli VA, Mandanici E, Tini MA, Borgatti L. 2015. Terrestrial Remote Sensing techniques to complement conventional geomechanical surveys for the assessment of landslide hazard: The San Leo case study (Italy). *European Journal of Remote Sensing* **48** : 639–660. DOI: 10.5721/EuJRS20154835
- Starodubtsev VM. 2012. Impact of Bugun’ water reservoir on coast for 50 years. *Arid Ecosystems* **2** : 132–138. DOI: 10.1134/S2079096112020102
- Tsai Z-X, You GJ-Y, Lee H-Y, Chiu Y-J. 2012. Use of a total station to monitor post-failure sediment yields in landslide sites of the Shihmen reservoir watershed, Taiwan. *Geomorphology* **139–140** : 438–451. DOI: 10.1016/j.geomorph.2011.11.008
- Usmanov B, Nicu IC, Gainullin I, Khomyakov P. 2018. Monitoring and assessing the destruction of archaeological sites from Kuibyshev reservoir coastline, Tatarstan Republic, Russian Federation. A case study. *Journal of Coastal Conservation* **22** : 417–429. DOI: 10.1007/s11852-017-0590-9
- Viero A, Teza G, Massironi M, Jaboyedoff M, Galgaro A. 2010. Laser scanning-based recognition of rotational movements on a deep seated gravitational instability: The Cinque Torri case (North-Eastern Italian Alps). *Geomorphology* **122** : 191–204. DOI: 10.1016/j.geomorph.2010.06.014
- Wang X, Pedrycz W, Niu R. 2015. Spatio-temporal analysis of Quaternary deposit landslides in the Three Gorges. *Natural Hazards* **75** : 2793–2813. DOI: 10.1007/s11069-014-1462-3
- Wilkinson MW, Jones RR, Woods CE, Gilment SR, McCaffrey KJW, Kokkalas S, Long JJ. 2016. A comparison of terrestrial laser scanning and structure-from-motion photogrammetry as methods for digital outcrop acquisition. *Geosphere* **12** : 1865–1880. DOI: 10.1130/GES01342.1
- Yermolaev O, Usmanov B. 2014. The basin approach to the anthropogenic impact assessment in oil-producing region. paper presented at the International Multidisciplinary Scientific GeoConference Surveying Geology and Mining Ecology Management, SGEM, 681–688. DOI: 10.5593/SGEM2014/B52/S20.090
- Yermolaev O, Usmanov B, Muharamova SS. 2015. The basin approach and mapping to the anthropogenic impact assessment on the east of the Russian plain. *International Journal of Applied Engineering Research* **10** : 41178–41184
- Yermolaev OP. 2017. Geoinformation mapping of soil erosion in the Middle Volga region. *Eurasian Soil Science* **50** : 118–131. DOI: 10.1134/S1064229317010070
- Yermolaev OP, Gafurov AM, Usmanov BM. 2018. Evaluation of Erosion Intensity and Dynamics Using Terrestrial Laser Scanning. *Eurasian Soil Science* **51** : 814–826. DOI: 10.1134/S1064229318070037
- Zang Y, Yang B, Li J, Guan H. 2019. An Accurate TLS and UAV Image Point Clouds Registration Method for Deformation Detection of Chaotic Hillside Areas. *Remote Sensing* **11** : 647. DOI: 10.3390/rs11060647

Zhang Y, Zhu S, Tan J, Li L, Yin X. 2020. The influence of water level fluctuation on the stability of landslide in the Three Gorges Reservoir. *Arabian Journal of Geosciences* **13** : 845. DOI: 10.1007/s12517-020-05828-3

TABLES

Table 1. Number (#) of laser scanning points at Site 1.

Scan date	Site 1 (#)
July 2012	1 847 951
November 2012	2 271 130
July 2013	850 394
November 2013	1 509 131
June 2014	1 550 689

Table 2. Dates and data acquisition techniques for Site 1

2012	Laser Scan - July, November
2013	Laser Scan - July, November
2014	Laser scanning - June
2019	UAV - August

Table 3. Point clouds georeferencing errors for site 1.

Point	Manual Point Selection	Manual Point Selection	Manual Point Selection	Iterative Closest Point method (ICP)
	X	Y	Z	X
1	0.09	-0.18	0.63	-0.05
2	-0.45	0.09	0.18	0.10
3	0.09	0.27	-0.36	0.00
4	0.27	-0.36	0.45	-0.04
5	0.36	0.45	-0.54	-0.11
6	0.54	0.27	0.09	0.06
7	-0.18	0.09	0.09	-0.03
<b>Total</b>	<b>0.28</b>	<b>0.24</b>	<b>0.33</b>	<b>0.06</b>

Table 4. Dates and data acquisition techniques and sources for Site 2.

1958	Aerial image
1975	"Corona" satellite image
1985	Aerial image
1987	Aerial image
1993	Aerial image
2002	Total Station Survey
2003	Total Station Survey
2005	Total Station Survey
2006	Total Station Survey
2010	Roscosmos image
2019	UAV data

Table 5. Quantitative indices describing the intensity of geomorphic processes at Site 1 according to scanning results.

Observation period	Abrasion scarp $V_-/S^*$ , $m^3/m^2$	Abrasion scarp $V_+/S^*$ , $m^3/m^2$	Upper part of the slope $V_-/S$ , $m^3/m^2$
06/ 2012 - 11/ 2012	0.08	0.25	0.06
11/ 2012 - 06/2013	0.67	0.06	0.2
<b>06/ 2012 - 07/2013*</b>	<b>0.54</b>	<b>0.05</b>	<b>0.25</b>
07/2013 - 11/ 2013	0.02	0.02	0.08
11/ 2013 - 06/ 2014	0.03	0.69	0.08
<b>07/2013 - 06/ 2014</b>	<b>0.07</b>	<b>0.61</b>	<b>0.17</b>

\*  $V_-/S$  represents the eroded soil volume per unit area;  $V_+/S$  refers to the deposited soil volume per unit area.

\*\* The annual average values of eroded and accumulated volumes are in bold

Table 6. Quantitative indicators characterizing the intensity of geomorphic processes at site 1 based on UAV survey results.

Observation period	$V_+/S^*$ , $m^3/m^2$	$V_-/S^*$ , $m^3/m^2$	$\Delta V/S$ , $m^3/m^2$
06/ 2012 - 11/ 2012	0.008	0.017	-0.009
11/ 2012-7/2013	0.014	0.036	-0.023
<b>06/ 2012 - 07/2013**</b>	0.012	0.044	-0.033
7/2013-11/2013	0.003	0.022	-0.019
11/2013-6/2014	0.014	0.026	-0.012
<b>07/2013 - 06/ 2014</b>	0.009	0.040	-0.031
<b>6/2014-8/2019</b>	0.000	0.038	-0.038

\*  $V_-/S$  represents the eroded soil volume per unit area;  $V_+/S$  refers to the deposited soil volume per unit area.  
 $\Delta V/S$  is the net soil loss

\*\* The annual average values of eroded and accumulated volumes are in bold

Table 7. Retreat rate of the landslide scarp at Site 2. See also figure 11.

Year	Retreat rate (m/year)	
	Mean	Maximum
1975	1.89	2.12
1985	1.45	1.92
1987	8.73	11.29
1993	3.50	6.38
2002	1.28	2.67
2003	1.35	2.57
2005	1.28	2.43
2006	1.34	2.49
2010	1.12	2.04
2019	0.84	1.38

## LIST OF FIGURES

Figure 1. Location of the Kuibyshev reservoir on the Volga river and the two study sites in the East of the Russian Plain.

Figure 2. Aerial (2019) and oblique views of the shoreline and the landslide body at Site 1.

Figure 3. Aerial view (2019) of Site 2 with landslide polygon.

Figure 4. Views on the landslide at Site 2 in 2003 (A) and in 2019 (B)

Figure 5. Used scanning equipment - Trimble GX (A) and point clouds for Site 1 (2014) (B)

Figure 6. Site 1. Part of the study area in November 2013 (A) and June 2014 (B). The white line shows a block landslide, and the yellow line shows an abrasion scarp.

Figure 7. Variability of total month precipitation  $>10 \text{ mm}\cdot\text{month}^{-1}$  for the summer-fall periods of 2012 and 2013 at the study sites.

Figure 8. Site 1. 3D-model (2019) with location (A) of slope profiles 1 (B) and 2 (C) of the abrasion-slope at site 1

Figure 9. Site 1. Slope profile changes at site 1 in the period 2012-2019 (blue line) and 2014-2019 (green)

Figure 10. Site 2 depicted on the aerial images of 1958 (A), 1985 (B), and 1987 (C)

Figure. 11. Site 2. Digital Globe image (2020). Evolution of landslide scarp edge and shoreline between 1958 and 2019

Figure 12. Evolution of the annual landslide scarp retreat rate at Site 2 since 2002, when high-precision instrumental fieldwork began.

















